

FS350M-4

Industrial AM Production Economy

▶ www.farsoon.com



HIGHLY PRODUCTIVE SYSTEM

Featuring an expanded build cylinder of 433×358×400mm, the FS350M-4 is capable of producing large metal parts from a wide range of powder materials. With quad 500-watt lasers configuration and thicker layer process, the FS350M-4 enhances the build efficiency for industrial scale series production.

EFFICIENCY + SAFETY

Equipped with advanced multi-laser scanning strategy and calibration algorithms, the FS350M-4 offers optimal build efficiency, and uniformed part performance in overlapping areas. The closed-loop Powder Management System, intelligent recoating control, and advanced layered gas flow design allow for efficient, yet uniformed melting process of metal powder.

COST PERFORMANCE + OPEN

The FS350M-4 features a machine footprint as small as 6.03 sqm with an integrated three-stage Filtration System. In an additive factory setting, FS350M-4 enables high density layout to achieve maximum throughput per floor area at economical additive production cost. Like all Farsoon machines, the FS350M-4 is a truly open platform which offers the user a high degree of control to tailor processing parameters for industrial application requirements and cost-competitive metal additive manufacturing.



Provided
by:

NovaStar
SOLUTIONS

FS350M-4

FARSOON FS350M-4

TECHNICAL DATA	FS350M-4
External Dimensions (L×W×H)	3260×1850×2300 mm (128.3×72.8×90.6 in)
Build Cylinder Size¹ (L×W×H)	433×358×400 mm (17.1×14.1×15.7 in) (Height incl. build plate)
Net Weight	Approx. 3300kg (7275.3 lb)
Layer Thickness	0.02~0.1 mm (0.0008-0.0039 in)
Scanning Speed	Max. 10 m/s (32.8 ft/s)
Laser Type	Quad Lasers, 4×500W
Scanner	F theta lenses
Inert Gas Protection	Argon/Nitrogen
Average Inert Gas Consumption in Process	3-5 L / min
Operating System	64 bit Windows 10
Comprehensive Software	BuildStar, MakeStar®
Key Software Features	Open machine key parameters, real-time build parameter modification, three-dimensional visualization, diagnostic functions
Data File Format	STL
Power Supply	EUR/China: 400V±10%, 3~N/PE, 50Hz, 42A US: transformer sold with machine
Operating Ambient Temperature	22-28°C (71.6-82.4°F)
Materials²	316L, AISi10Mg, Ti6Al4V, 17-4PH, ST1, Maraging Steel Grade 300, more materials to come

¹ The functional build volume depends on the parts/materials.

² The materials marked with * are in the build process development.

Many factors may affect the performance characteristics of products. We recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. Farsoon makes no warranties of any type, express or implied, including but not limited to, the warranties of merchantability or fitness for a particular use. This also applies regarding the consideration of possible intellectual property rights as well as laws and regulations. Farsoon reserves the right to change the technical data without notice. Farsoon®, BuildStar®, MakeStar® are registered trademarks of Farsoon Technologies. Last Change: 2023-09



PART: SHOE MOLD
SYSTEM: FS350M-4
MATERIAL: 316L

Novastar Solutions | 734.453.8003 | info@novastar.net | www.novastar.net | 35200 Plymouth Rd. Livonia, MI. 48150

AMEA Farsoon Technologies Co., Ltd. | +86.731.8397.6198 | globalinfo@farsoon.com | No. 181 Linyu Road, Changsha National High-Tech Industrial Zone, Hunan, China

AMERICAS Farsoon Americas CORP. | +1 512-551-9901 | contact@farsoonam.com | 3161 Eagles Nest Street, Suite 350, Round Rock, TX 78665

www.farsoon.com